



LG 306 is a lawn and garden tire suitable for mowers. In some sizes, LG 306 is also fit for transport operations with airport cruise cars and small tractors in municipality/maintenance applications. The specific tread pattern makes the tire gentle on the ground, easing handling at the same time. LG 306 is available in an "aramid-belted" version for users who need strengthened puncture resistance.

MACHINERY

 AGRICULTURE

MOWER - SMALL TRACTOR

APPLICATIONS

 AGRICULTURE

HAULAGE - LAWN & GARDEN MUNICIPALITY /
MAINTENANCE

PLUS



FIELD PROTECTION



DURABILITY



HANDLING

PRODUCT: LG 306



TECHNICAL DATA U/M: INTERNATIONAL STANDARD (MM)

| Size | Version | PR | RIM REC | SW | OD | SLR | RC | Type |
|-----------------|---------------|----|--------------------------------|-----|-----|-----|------|------|
| 11 X 4.00 - 5 | | 4 | 3.00 A | 104 | 272 | 120 | 789 | TL |
| 13 X 5.00 - 6 | | 4 | 3.50 A | 127 | 325 | 144 | 943 | TL |
| 13 X 5.00 - 6 | | 6 | 3.50 A | 127 | 325 | 144 | 943 | TL |
| 15 X 6.00 - 6 | | 4 | 4.50 A | 152 | 365 | 159 | 1059 | TL |
| 15 X 6.00 - 6 | | 6 | 4.50 A | 152 | 365 | 159 | 1059 | TL |
| 16 X 6.50 - 8 | | 4 | 5.375 I - 55 ; I - 70 ; I - 90 | 170 | 408 | 182 | 1183 | TL |
| 16 X 6.50 - 8 | | 6 | 5.375 I - 55 ; I - 70 ; I - 90 | 170 | 408 | 182 | 1183 | TL |
| 16 X 6.50 - 8 | ARAMID BELTED | 6 | 5.375 I - 55 ; I - 70 ; I - 90 | 170 | 408 | 182 | 1183 | TL |
| 16 X 6.50 - 8 | | 8 | 5.375 I - 55 ; I - 70 ; I - 90 | 170 | 408 | 182 | 1183 | TL |
| 18 X 8.50 - 8 | | 4 | 7.00 I - 55 ; I - 70 ; I - 90 | 215 | 450 | 198 | 1305 | TL |
| 18 X 9.50 - 8 | | 4 | 7.00 I - 55 ; I - 70 ; I - 90 | 230 | 470 | 206 | 1363 | TL |
| 18 X 8.50 - 8 | | 6 | 7.00 I - 55 ; I - 70 ; I - 90 | 215 | 450 | 198 | 1305 | TL |
| 18 X 9.50 - 8 | | 6 | 7.00 I - 55 ; I - 70 ; I - 90 | 230 | 470 | 206 | 1363 | TL |
| 18 X 8.50 - 8 | ARAMID BELTED | 6 | 7.00 I - 55 ; I - 70 ; I - 90 | 215 | 450 | 198 | 1305 | TL |
| 18 X 9.50 - 8 | ARAMID BELTED | 6 | 7.00 I - 55 ; I - 70 ; I - 90 | 230 | 470 | 206 | 1363 | TL |
| 20 X 10.00 - 8 | | 4 | 8.00 I - 55 | 254 | 508 | 221 | 1473 | TL |
| 20 X 10.00 - 8 | | 6 | 8.00 I - 55 | 254 | 508 | 221 | 1473 | TL |
| 20 X 10.00 - 8 | ARAMID BELTED | 6 | 8.00 I - 55 | 254 | 508 | 221 | 1473 | TL |
| 18 X 8.50 - 10 | | 4 | 7.00 I - 55 ; I - 70 ; I - 90 | 210 | 460 | 209 | 1340 | TL |
| 20 X 10.00 - 10 | | 4 | 8.00 I - 55 | 250 | 508 | 226 | 1473 | TL |
| 20 X 8.00 - 10 | | 4 | 6.00 I - 55 ; I - 70 ; I - 90 | 205 | 500 | 223 | 1450 | TL |
| 20 X 10.00 - 10 | | 6 | 8.00 I - 55 | 250 | 508 | 226 | 1473 | TL |
| 20 X 8.00 - 10 | | 6 | 6.00 I - 55 ; I - 70 ; I - 90 | 205 | 500 | 223 | 1450 | TL |
| 20 X 10.00 - 10 | ARAMID BELTED | 6 | 8.00 I - 55 | 250 | 508 | 226 | 1473 | TL |
| 23 X 10.50 - 12 | | 4 | 8.5 I - 55 | 260 | 585 | 262 | 1697 | TL |
| 23 X 8.50 - 12 | | 4 | 7.00 I - 55 ; I - 70 ; I - 90 | 210 | 575 | 258 | 1709 | TL |
| 23 X 10.50 - 12 | | 6 | 8.5 I - 55 | 260 | 585 | 262 | 1697 | TL |
| 23 X 8.50 - 12 | | 6 | 7.00 I - 55 ; I - 70 ; I - 90 | 210 | 575 | 258 | 1709 | TL |
| 23 X 10.50 - 12 | ARAMID BELTED | 6 | 8.5 I - 55 | 260 | 585 | 262 | 1697 | TL |
| 23 X 8.50 - 12 | ARAMID BELTED | 6 | 7.00 I - 55 ; I - 70 ; I - 90 | 210 | 575 | 258 | 1709 | TL |
| 23 X 10.50 - 12 | | 8 | 8.5 I - 55 | 260 | 585 | 262 | 1697 | TL |
| 23 X 8.50 - 12 | | 8 | 7.00 I - 55 ; I - 70 ; I - 90 | 210 | 575 | 258 | 1709 | TL |
| 23 X 10.50 - 12 | | 12 | 8.5 I - 55 | 260 | 585 | 262 | 1697 | TL |
| 23 X 8.50 - 12 | | 12 | 7.00 I - 55 ; I - 70 ; I - 90 | 210 | 575 | 258 | 1709 | TL |
| 24 X 12.00 - 12 | | 4 | 9.5 AT | 298 | 610 | 276 | 1774 | TL |
| 26 X 12.00 - 12 | | 4 | 10.50 I - 55 ; I - 70 ; I - 90 | 310 | 640 | 283 | 1856 | TL |
| 26 X 12.00 - 12 | ARAMID BELTED | 6 | 10.50 I - 55 ; I - 70 ; I - 90 | 310 | 640 | 283 | 1856 | TL |
| 26 X 12.00 - 12 | | 8 | 10.50 I - 55 ; I - 70 ; I - 90 | 310 | 640 | 283 | 1856 | TL |
| 26 X 12.00 - 12 | ARAMID BELTED | 8 | 10.50 I - 55 ; I - 70 ; I - 90 | 310 | 640 | 283 | 1856 | TL |
| 26 X 12.00 - 12 | | 12 | 10.50 I - 55 ; I - 70 ; I - 90 | 310 | 640 | 283 | 1856 | TL |
| 26 X 12.00 - 12 | | 14 | 10.50 I - 55 ; I - 70 ; I - 90 | 310 | 640 | 283 | 1856 | TL |
| 24 X 8.50 - 14 | | 4 | 7 JA | 210 | 610 | 280 | 1769 | TL |
| 25 X 8.50 - 14 | | 6 | 7.00 I - 55 ; I - 70 ; I - 90 | 220 | 638 | 286 | 1889 | TL |
| 27 X 10.50 - 15 | | 4 | 8.00 LB | 272 | 705 | 318 | 2042 | TL |
| 27 X 8.50 - 15 | | 4 | 7.00 JA | 216 | 680 | 308 | 1970 | TL |

PRODUCT: LG 306



TECHNICAL DATA U/M: INTERNATIONAL STANDARD (MM)

| Size | Version | PR | RIM REC | SW | OD | SLR | RC | Type |
|-------------------|---------|----|---------|-----|------|-----|------|------|
| 27 X 10.50 - 15 | | 12 | 8.00 LB | 272 | 705 | 318 | 2042 | TL |
| 31 X 15.5 - 15 | | 4 | 13 LB | 391 | 792 | 350 | 2313 | TL |
| 13.6 - 16 | | 4 | W 12 | 388 | 975 | 439 | 2793 | TL |
| 33 X 15.50 - 16.5 | | 10 | 12.00 | 396 | 840 | 374 | 2495 | TL |
| 38 X 14.00 - 20 | | 4 | W 11 | 375 | 980 | 435 | 2894 | TL |
| 44 X 18.00 - 20 | | 4 | W 14 L | 475 | 1180 | 543 | 3496 | TL |