

TR 315



TR 315 is suitable for muddy grounds in soil tillage and lawn and garden operations. It is ideal with implement machinery, trenchers and orchard harvesters. The TR 315 tire has a large contact area which provides excellent grip and outstanding stability in any condition.

MACHINERY

AGRICULTURE

IMPLEMENT MACHINERY - ORCHARD HARVESTER -
TRENCHER

APPLICATIONS

AGRICULTURE

LAWN & GARDEN - MUNICIPALITY / MAINTENANCE -
SOIL TILLAGE

PLUS



TRACTION



SUITABLE FOR MUDDY
GROUND



STABILITY

PRODUCT: TR 315



TECHNICAL DATA U/M: INTERNATIONAL STANDARD (MM)

Size	Version	PR	RIM REC	SW	OD	SLR	RC	Type
16 X 6.50 - 8		4	5.375 I - 55 ; I - 70 ; I - 90	155	408	182	1183	TL
16 X 6.50 - 8		6	5.375 I - 55 ; I - 70 ; I - 90	155	408	182	1183	TL
23 X 10.50 - 12		4	8½ JA	255	590	260	1682	TL
23 X 8.50 - 12		4	7 JA ; 7.00 I - 55 ; I - 70 ; I - 90	205	575	258	1668	TL
23 X 10.50 - 12		6	8½ JA	255	590	260	1682	TL
23 X 8.50 - 12		6	7 JA ; 7.00 I - 55 ; I - 70 ; I - 90	205	575	258	1668	TL
23 X 10.50 - 12		8	8½ JA	255	590	260	1682	TL
23 X 10.50 - 12		10	8½ JA	255	590	260	1682	TL
26 X 12.00 - 12		4	10½ JA	308	655	289	1905	TL
26 X 12.00 - 12		8	10½ JA	308	655	289	1905	TL
26 X 12.00 - 12		10	10½ JA	308	655	289	1905	TL
26 X 12.00 - 12	SPECIAL	10	10½ JA	308	655	289	1905	TL
26 X 12.00 - 12		12	10½ JA	308	655	289	1905	TL
31 X 15.50 - 15		8	13 LB	390	800	354	2320	TL
31 X 15.50 - 15		10	13 LB	390	800	354	2320	TL
31 X 15.50 - 15		12	10 LB	390	800	354	2320	TL