

Size	Load index	Speed symbol	Section Width (mm)	Diameter (mm) Overall	Static Loaded Radius (mm)	Rolling Circ. (mm) @ 90 km/h (Tot, ± 2%)	Rim (Inch) Measuring	Rim (Inch) Optional				dB			
DURAVIS R-TRAILER 002															
385/65 R 22.5	160	K	380	1086	502	3300	11.75	12.25	B	B	A	70	✓	✓	✓
	158	L													
385/55 R 22.5	160	K	389	1005	468	3055	12.25	11.75	B	B	A	70	✓	✓	✓
	158	L													
DURAVIS R-TRAILER 002 EVO															
385/65 R 22.5	164	K	381	1081	500	3285	11.75	12.25	B	B	A	70	✓	✓	✓
	158	L													

DURAVIS R-TRAILER 002

DURAVIS R-TRAILER 002 EVO



- Low deformation pattern design for high robustness and reduced energy loss.
- Best-in-class wet grip ¹⁾ thanks to optimised contact pressure and enhanced water ejection.
- Optimised fuel efficiency ²⁾ thanks to high performing compound and high compression stiffness.
- Equipped with unique RFID technology to identify the tyres.
- Robust casing for longer tyre life and great retreadability.

1) An EU label grade "A" in steer (size: 315/80r22.5)

2) Features B-C-B combination in steer, drive and trailer EU label in sizes 315/80r22.5 steer & drive and 385/65r22.5 in trailer.

