



STEER

ECOPIA H-STEER 002

Size	Load index	Speed symbol	Section Width (mm)	Diameter (mm) Overall	Static Loaded Radius (mm)	Rolling Circ. (mm) @ 90 km/h (Tol, ± 2%)	Rim (inch) Measuring	Rim (inch) Optional				dB	M+S		
ECOPIA H-STEER 002															
295/80 R 22.5	154/149	M	306	1046	487	3179	9.00	8.25	B	B	A	71	✓	✓	✓
315/80 R 22.5	156/150	L	314	1069	497	3251	9.00	9.75	B	B	A	69	✓	✓	✓
	154/150	M													
315/70 R 22.5	156/150	L	313	1009	466	3067	9.00	9.75	A	B	A	68	✓	✓	✓
	154/150	M													
385/65 R 22.5	160	K	376	1073	496	3261	11.75	12.25	A	B	B	72	✓	✓	✓
	158	L													
315/60 R 22.5	154/148	L	322	955	447	2903	9.75	9.00	B	B	B	72	✓	✓	✓
385/55 R 22.5	160	K	386	995	464	3024	12.25	11.75	A	B	A	71	✓	✓	✓
	158	L													
355/50 R 22.5	156	L	381	928	435	2821	11.75	-	C	B	A	70	✓	✓	✓



- Low deformation pattern and NanoPro-Tech™ compound for best in class fuel efficiency.
- Top rated wet grip¹⁾ thanks to high effective contact area.
- Winter compliant with 3PMSF and M+S markings.
- Robust casing for longer tyre life and great retreadability.
- Equipped with unique RFID technology to identify the tyres.

1) B-B-B COMBINATION ON STEER, DRIVE, TRAILER of EU label grades in sizes 315/70R22.5 and 385/55R22.5.

