

/ HIGHWAY TRAILER

ECOPIA H-TRAILER 002



Size	Load index	Speed symbol	Section Width (mm)	Diameter (mm) Overall	Static Loaded Radius (mm)	Rolling Circ. (mm) @ 90 km/h (Tol. ± 2%)	Rim (Inch) Measuring	Rim (Inch) Optional				dB	M+S		
445/45 R 19.5 ¹⁾	160	J	429	906	420	2754	15.00	14.00	B	A	B	72	✓	✓	
385/65 R 22.5 ¹⁾	160	K	379	1078	498	3277	11.75	12.25	A	B	A	68	✓	✓	✓
	158	L													
385/55 R 22.5 ¹⁾	160	K	391	997	464	3031	12.25	11.75	A	B	A	68	✓	✓	✓
	158	L													

- Low deformation pattern and NanoPro-Tech™ compound for best in class fuel efficiency.
- Top rated wet grip ²⁾ thanks to increased contact area and excellent water evacuation.
- Winter compliant with 3PMSF and M+S markings.
- Robust casing for longer tyre life and great retreadability.
- Equipped with unique RFID technology to identify the tyres.



1) FRT marked tyre.

2) B-B-B COMBINATION ON STEER, DRIVE, TRAILER of EU label grades in sizes 315/70R22.5 and 385/55R22.5.