

R-TRAILER 001

Size	Load index	Speed symbol	Section Width (mm)	Diameter (mm) Overall	Static Loaded Radius (mm)	Rolling Circ. (mm) @ 90 km/h (Tol, ± 2%)	Rim (inch) Measuring	Rim (inch) Optional				dB	M+S		
205/65 R 17.5 ¹⁾	132/130	J	205	715	336	2173	6.00	6.75	C	C	A	69	✓	✓	✓ ²⁾
	133/133	F													
215/75 R 17.5 ¹⁾	136/134	K	212	776	363	2359	6.00	6.75	C	C	A	69	✓	✓	✓ ²⁾
235/75 R 17.5 ¹⁾	143/141	J	238	807	376	2453	6.75	7.50	C	B	A	68	✓	✓	✓ ²⁾
	144/144	F													
245/70 R 17.5 ¹⁾	143/141	J	251	797	368	2423	7.50	6.75	C	B	A	69	✓	✓	✓ ²⁾
	146/146	F													
245/70 R 19.5 ¹⁾	141/140	J	251	845	392	2568	7.50	6.75	C	B	A	69	✓	✓	✓ ²⁾
265/70 R 19.5 ¹⁾	143/141	K	250	872	403	2651	7.50	8.25	C	B	A	69	✓	✓	✓ ²⁾
285/70 R 19.5 ¹⁾	150/148	J	269	890	410	2705	8.25	7.50/9.00	C	B	A	69	✓	✓	✓ ²⁾



- Versatile trailer tyre designed for low platform trailers and car carriers.
- Robust casing construction combined with long lasting tread.
- Improved wet and snow grip.

1) FRT marked tyre.

2) Implemented with RFID within 2023.

