

/ URBAN BUS ALL POSITION

U-AP 002



Size	Load index	Speed symbol	Section Width (mm)	Diameter (mm) Overall	Static Loaded Radius (mm)	Rolling Circ. (mm) @ 90 km/h (Tol. ± 2%)	Rim (Inch) Measuring	Rim (Inch) Optional				dB	M+S		
215/70 R 17.5	128/126	M	215	772	361	2347	6.00	6.75	C	C	A	67	✓	✓	
245/70 R 19.5	136/134	L	242	846	392	2572	7.50	6.75	C	C	A	70	✓	✓	
265/70 R 19.5	140/138	M	252	864	400	2626	7.50	6.75/8.25	C	C	A	69	✓	✓	
275/70 R 22.5	152/149	J	283	959	446	2915	8.25	7.50	B	B	A	69	✓	✓	✓
	150/149	K													
315/60 R 22.5	154/148	L	314	957	448	2909	9.75	9.00	C	C	A	70	✓	✓	✓

The ideal bus tyre for sustainable urban mobility

- Enjoy a quiet ride, reduced CO₂ emissions ¹⁾, and strong casing allowing multiple lives.
- A 9% longer tyre life ensures excellent mileage ²⁾.
- Suitable with all kinds of powertrains (High load capacity).
- Reinforced sidewall provides extra protection.



1) Based on official qualification tests which was carried out in Bridgestone facilities vs predecessor U-AP 001 Size 275/70 R22.5, All Position. Reduction to B Grade for RRC vs U-AP 001 (D Grade). Reduction to 69 dB vs U-AP 001 (71dB).

2) Based on internal field test (MTF801) carried out vs predecessor U-AP 001 Size 275/70 R22.5, All Position.

3) Implemented with RFID within 2023.