

ATU 410



Salient Features

- Heavy duty application for Backhoe machines.
- Good self-cleaning properties.
- Strong and sturdy heavy duty nylon plies for longer service durability.
- Cuts and cracks resistant tread compound for increased service life.

Applications

Backhoe

Dozer

Grader

SIZES

SIZE	PR	TYPE	RIM		O.D (mm)	S.W (mm)	SLR (mm)	RC (mm)	LI/SS (LLV)	MAX. LOAD (LLV)		PRESSURE (bar)	LI/SS (HLV)	MAX. LOAD (HLV)		PRESSURE (bar)
			REC.INCH	ALT.INCH						30KMPH (Kgs)	40KMPH (Kgs)			30KMPH (Kgs)	40KMPH (Kgs)	
10.5/80-18	8	TL	W9	W8, W9	907	274	406	2667	127A6/123A8	1750	1550	3.0	134A6/130A8	2120	1900	3.6
10.5/80-18	10	TL	W9	W8, W9	907	274	406	2667	131A6/127A8	1950	1750	3.7	138A6/134A8	2360	2120	4.4
10.5/80-18	12	TL	W9	W8, W9	907	274	406	2667	135A6/131A8	2180	1950	4.3	141A6/137A8	2575	2300	5.3
10.5/80-18	14	TL	W9	W8, W9	907	274	406	2667	138A6/134A8	2360	2120	5.4	144A6/140A8	2800	2500	6.5
12.5/80-18	10	TT/TL	W9	11.0	980	308	438	2896	139A6/135A8	2430	2180	3.1	145A6/141A8	2900	2575	3.8
12.5/80-18	12	TT/TL	W9	11.0	980	308	438	2896	142A6/138A8	2650	2360	3.7	148A6/144A8	3150	2800	4.4
12.5/80-18	14	TT/TL	W9	11.0	980	308	438	2896	145A6/141A8	2900	2570	4.3	151A6/147A8	3450	3075	5.2
12.5/80-18	16	TT/TL	W9	11.0	980	308	438	2896	148A6/144A8	3150	2800	4.9	154A6/150A8	3750	3350	5.9